



WAB Artykuły Poligraficzne

ul. Ceramiczna 7 • 20-150 Lublin • tel (+48 81) 740 94 94 • fax (+48 81) 740 94 95

ul. Owocowa 10E • 40-158 Katowice
tel (+48 32) 601 21 50 fax(+48 32) 601 21 95 •

TECHNICAL DATA SHEET

Coating Plate with higher resistance to UV Varnishes

- new generation of coating plates for all sheetfed applications
- 100% solvent free production
- poliester backed, bi-directional and strippable plates
- very regular microground and polished surface
- superior quality of compressible layer (1,95 – 2,35mm)
- superior varnish lay-down achieving incredibly high gloss level
- long lasting plates with excellent re-use rates
- compatible with CAD and manual cutting
- essential and High-Tech construction for superior stability, varnish transfer and easy stripping

TECHNICAL DATA

Colour	Grey
Nominal thickness mm (tolerance +/- 0,02mm)	1,15 - 1,35 - 1.95 mm
Carrier	Polyester
Thick. Of carrier	0,35 mm
Bi-directional	YES
Compressible layer	1,15 mm NO 1,35 mm NO 1,95 mm YES
Thick. Of compressible layer	1,95 mm – 0,6 mm
Roughness (Ra: µm)	0,5-0,7
Coating compatibility	UV

