



WAB Polygraphic Materials

Ceramiczna 7 ◦ 20-150 Lublin, Poland ◦ ph. (+48 81) 740 94 94 ◦ Fax (+48 81) 740 94 95

Owocowa 10E ◦ 40-158 Katowice, Poland
ph. (+48 32) 601 21 50 Fax (+48 32) 601 21 95 ◦

TECHNICAL DATA SHEET

PC ECO SEMI FRESH

Characteristics

PC ECO SEMI FRESH is SemiFresh type ink of high pigmentation. It has a good gloss, good rub resistance (rub resistance depends on the quality of the printing substrate) and fast drying.

Application

Multipurpose ink of high printability may be applied on various substrates (coated papers, coated cardboard). When used for printing on cardboard then varnishing is recommended.

Additional information

A wide range of application is a big advantage of **PC ECO SEMI FRESH**. It can be used for printing of magazines, advertisements.

Resistance features	Light fastness	Nitro	Alkali	UV varnishing / acryl varnish
YELLOW	5	+	+	+
RED	4	+	-	-
CYAN	8	+	+	+
BLACK	7	-	-	limited*

+ resistance

- lack of resistance

* limitation refers to UV varnish for colour adjustment

Light fastness according to DIN 16525, from 1 (low) to 8 (high)