

*Rely on us.*SM

Novaboard® C 990 PROTECT BIO

The rub-resistant series in BIO-quality for perfecting

K+E® standard process inks for sheetfed offset

Product Features

- Novaboard® C 990 PROTECT BIO is a colour-intense, very rub-resistant process ink series, based on renewable raw materials, with very fast oxidative drying properties. The series is completed by a special black - Novaboard® 992 PROTECT LT BIO - which is especially formulated for use on very picking sensitive substrates.
- It is optimally suited for perfecting on fast running multi-colour printing presses.
- Due to a new binder system an excellent ink-water stability is combined with reduced misting properties especially at high printing speeds.

Advantages of Novaboard® C 990 PROTECT BIO

- Highest rub resistance.
- Very well suited for all kind of substrates – especially for picking sensitive papers.
- Fastest oxidative drying.
- Rapid and reliable further processing.
- Excellent printability also on perfecting presses.
- Newest binder technology with optimised ink-water stability.
- High process stability.



FlintGroup

Novaboard® C 990 PROTECT BIO



	Fastness properties					Printing properties								
	Light fastness	Alcohol	Solvent mixture	Alkali	Hot-calendering	Dot gain	Gloss	Setting	Oxidative drying	Rub resistance	Rapid further processing	Suitability for gloss coated papers/board	Suitability for uncoated papers/board	Suitability for matt coated papers/board
Novaboard® C990						6	6	5	6	7	6	7	7	7
Novaboard® 1 C 990 PROTECT BIO Yellow	5	+	+	+	+	1 = Characteristic weakly expressed 7 = Characteristic strongly expressed								
Novaboard® 2 C 990 PROTECT BIO Magenta	5	+	+	-	+	<p>The assessment of the colour properties was made under standardised printing conditions. In individual cases, under special conditions, as in printing with very high ink densities, the classification of certain properties may be different.</p>								
Novaboard® 4 C 990 PROTECT BIO Cyan	8	+	+	+	+									
Novaboard® 990 PROTECT BIO Black, fast blue-toned	8	+	+	+	+									
Novaboard® 992 PROTECT LT BIO Black, fast blue-toned	8	+	+	+	+									
	<p>Light fastness properties according to ISO 12040: from 1 (low) to 8 (high)</p> <p>Fastness properties according to ISO 2836: + = Resistance provided - = Resistance not provided</p>													

Drying properties

Partly duct-fresh.

Substrates

Optimally suited for matt, gloss coated papers as well as uncoated papers and board.

Remarks

Due to its partly duct-fresh setting, Novaboard® C 990 PROTECT BIO provides an excellent compromise between conventional duct-fresh and oxidative drying. Thanks to the low tack property the series is ideally suited for all kind of substrates, particularly for picking sensitive papers. Novaboard® 992 PROTECT LT BIO Black is recommended for use on very picking sensitive papers. Suited for printing work corresponding to ISO 12647-2.

Exceptions

Not for use on food packaging without functional barrier.

More products. Streamlined access. Greater results.

Flint Group offers a uniquely powerful combination of products, services and expertise; giving you access to the industry's broadest range of pressroom products.

Inks & Coatings. Pressroom Chemicals. Blankets. Sleeves. Consumables.

Rely on us for consistency, reliability and customer focus. Our aim is to make it easier for you to achieve your business goals. With Flint Group products in your pressroom, you can run your business with confidence and peace of mind.

You are welcome to contact us for further information.

The aim of our technical documents is to inform our customers about general values. However, the transferability of general values known from experience and laboratory results to concrete practical applications depends on a number of factors which are beyond our control. We therefore ask for your understanding that this advice document cannot be used as the basis for claims in law. Furthermore, the correct application for each product has to be checked carefully for suitability.

Flint Group
Packaging & Narrow Web
Sieglesstrasse 25
70469 Stuttgart, Germany

T +49 711 98 16-0
F +49 711 98 16-700
printmedia.eu@flintgrp.com
www.flintgrp.com

Product names followed by ® are trademarks registered by Flint Group Germany GmbH.